

Aluminium manual attack resistant doors

Fichet's manual attack resistant doors have been designed to satisfy the ever increasing need to protect people, property and assets from theft and attack, whilst maintaining an elegant appearance.

The MagTek A range is made up of enhanced manual attack resistant doors to protect against vandalism. It also features fully certified doors that have been tested by independent bodies in accordance with the relevant European standards. This way, Fichet can be sure of meeting all client requirements and expectations, providing a solution that offers the right protection against the identified risk.

Since aluminium is a material that is easy to shape and form, the MagTek A is an optimal solution that combines design and functional requirements.

The ease with which they can be integrated into buildings and the wide range of design choices available (dimensions, finishes and colours) mean that MagTek A doors are versatile, and can be used for both building refurbishments and new constructions.

The MagTek A range also includes a selection of partitions so that complete facade or enclosure solutions can be designed.



Material

Framework	Extruded aluminium profile with the inclu- sion of special steel armour depending upon the resistance level
Infill	Laminated security glass or solid infill made of an aluminium panel on the attack side and white colour laminate on the secure side
Finish	Powder coat to RAL 9010, 9006, 7035 or 7037

Standard equipment

Locking	3-point mechanical Euro Lock
Handle	Pad handle on both sides

Construction

Opening	Up to 150° inward and outward (depending on model)			
DIN	Left or right			
Clear opening	900mm at 90° opening			

Reference standard

The certified manual attack resistant range is tested to EN 1627 for the complete doorset. Standard EN 1627 includes 3 level of tests. The physical attack component which includes different sets of tools and attack times is in accordance with EN 1630.

Models

- Enhanced Manual Attack Resistant Doors MagTek A0 Lite
- Certified Manual Attack Resistant Doors MagTek A3 to A5

Options


- · Alternative RAL colours or anodised finish
- · Door position contact switch
- Electric lock
- Push buttons
- · Choice of handle types
- · Anti-panic bar (depending upon model)
- · Upgrade to bullet resistance


KEY FEATURES


- Elegant appearance.
- Resistance against manual attack.
- Wide range of finishes and dimensions available.
- Complementary windows and partitions.

Range composition

MagTek A0 Lite












MagTek A3 Lite



MagTek A3/MagTek A4










A3-S |

A4-S



A3-S | A4-S double leaf





A5-S









Standard technical specifications

Model	Туре	Rating	Leaf options	Total standard width: W (Single/ Double) (mm)	Total standard height: H (mm)	Aluminium framework	Infill
MagTek A0-S Lite	Enhanced Manual Attack		Single/ Double	1100/ 2100	2130	60mm thick	Solid
MagTek A0-G Lite	Resistant Doors	-					Glazed
MagTek A3- S Lite	Level 3	Level 3 to	Singlo	1100	2130	60mm thick	Solid
MagTek A3-G Lite		prEN 1627-30	Single				Glazed
MagTek A3-S		Level CR3 to	Single/	1150/	2130	80mm thick	Solid
MagTek A3-G	Certified Manual Attack	EN 1627-30	Double	2150			Glazed
MagTek A4-S	Resistant Doors		Single/	1150/ 2150	2130	80mm thick	Solid
MagTek A4-G	EN 1627-3	EN 1627-30	0				Glazed
MagTek A5-S	Level CR5 to EN 1627-30	Single/	1150/			Solid	
MagTek A5-H			Double	2150	2130	80mm thick	Partially glazed

Optional technical specifications


Model	FB3 bullet resistance	FB4 bullet resistance	FB5 bullet resistance	FB6 bullet resistance	Non standard width (mm)	Non standard height (mm)	Electric locking
MagTek A0-S Lite					750–1300 /	2000 2250	0
MagTek A0-G Lite	-	-	-	-	1300–2400	2090–2350	0
MagTek A3- S Lite					850–1250	2090–2330	
MagTek A3-G Lite		-	-	-	000-1200	2090–2330	-
MagTek A3-S	0	0	0	0	850–1300 /	2090–2350	0
MagTek A3-G	v	ř	Ť	Ť	1300–2400		
MagTek A4-S	0	0	0	0	850–1300 /	2090–2350	0
MagTek A4-G	0	0	U	U	1300–2400	2000-2000	U
MagTek A5-S					850–1300 /	0000 0050	
MagTek A5-H	0	0	0	0	1300–2400	2090–2350	•

Standard
Optional
- Not available


Dimensions (mm)


	Door	W Overall Width	PW Passage Width (90°)	COW Clear opening width	H Overall Height	PH Passage Height
MagTek A Lite (60 mm-thick)	Single	W	W–200	W–150	н	H–75
	Double	W	W–250	W–150	Н	H–75
MagTek A (80 mm-thick)	Single	W	W–250	W–180	Н	H–90
	Double	W	W–310	W–180	Н	H–90

RW reserved Width/RH Reserved Hight				
MASONERY (stone or concrete) W +10mm/H +10mm				
Metallic structure	W + 5 mm / H + 5 mm			









Notice:

- Product performance depends on how well it is installed. All installation details are provided in the MagTek A installation manual.
- Any modification of a certified doorset by adding a non factory-fitted device may result in the loss of certification. Contact Fichet for
- more information.
- Certificates for manual attack resistance are available on demand. Contact Fichet for any certificate requests.
- Any MagTek A door can be upgraded to a MagTek Plus intelligent door. Refer to the DorTek Plus product data sheet for more information.

LO GIUDICE MERFORI SRL Via del Gonfalone 3, Milano Tel: +39 0230556020



info@logiudicemerfori.com www.logiudicemerfori.com